

## PRODURAN® TAPS FROM THE DURAN GROUP

The perfect solution for metering and controlling gases and fluids

A fine-thread spindle permits extremely fine height adjustment of the tap opening. In combination with heavy-wall side-arms PRODURAN® taps from the DURAN Group are suitable for high vacuum applications.

The composite system of DURAN® glass, metal and plastic permits grease-free working, the media only coming into contact with DURAN® glass and PTFE. The tap's design makes it convenient to use and easy to undo and remove.

A safety device prevents the tap shaft from being accidentally unscrewed completely whilst the adjustable tap shaft increases the stopcock service life.

### PRODURAN® taps meet highest requirements:

- Vacuum-tight with a leak-rate of  $< 1 \times 10^{-6}$  mbar x l/s
- Precise dosing due to fine thread
- Safety thanks to unscrewing protection

PRODURAN® taps are available as angled or straight versions.

### PRODURAN® straight version

Cat. No.	Passage / mm	Pack / Quantity
28 605 580	0 – 2.5	10
28 605 600	0 – 4	10
28 605 620	0 – 6	10
28 605 640	0 – 10	10



### PRODURAN® 90° angled version

Cat. No.	Passage / mm	Pack / Quantity
28 605 660	0 – 2.5	10
28 605 680	0 – 4	10
28 605 700	0 – 6	10
28 605 710	0 – 10	10

